



Product: EMI Gasket Materials



Related Web Page:

<https://www.newtoplsrinjection.com>

Newtop Value Proposition:

Design & Engineering

Staff engineers comprehend design challenges and are available to help select materials and manufacturing processes that best fit specific application needs.

Material Solutions

Newtop Elastomerics has strategically partnered with industry leaders such as Rogers Corp., Saint-Gobain, 3M, Wacker Silicones and Momentive Silicones to ensure the highest quality materials are used. Newtop Elastomerics has a comprehensive inventory of engineered materials designed and manufactured to meet requirements of the most demanding gasketing applications.

Pre-Production through Manufacturing

Combining in-house CNC die cutting, waterjet cutting, injection molding, compression molding and adhesive lamination with comprehensive inventory, Newtop Elastomerics can fulfill fast-turn prototyping, pre-production and full production requirements.

SNE-553

Compound: 30 Durometer Conductive Silicone Rubber with Nickel / Graphite Filler

Product Description:

SNE-553 is a soft silicone polymer with nickel coated graphite particle fill, giving it very good shielding and grounding properties. High performance and competitively priced, SNE-553 makes an excellent option for commercial and military EMI applications.

Newtop Elastomerics offers pre-production and full production parts made from SNE-553, including waterjet cutting, die cutting or molding. 3M conductive adhesive backing is also available for cut parts and select molded parts.

Property	Typical Value
Durometer , Shore "A", (+/- 5)	30
Volume Resistivity , ohm-cm	0.125
Tensile Strength , minimum, psi	100
Elongation , min %	400
Temperature Low , °C (°F)	-60 (-76)
Temperature High , °C (°F)	200 (392)
Specific Gravity	1.70
Color	Black
Mil-G-83528	N/A
Available Configurations	<ul style="list-style-type: none"> • Sheets • Cut Parts (Waterjet/Die Cut) • Molded Parts • Conductive Adhesive Backed

Request Quote