

## **XIAMEN NEWTOP MATERIAL COMPANY**

**Product: EMI Gasket Materials** 



#### Related Web Page:

https://www.newtoplsrinjection.com

#### Newtop Value Proposition:

#### **Design & Engineering**

Staff engineers comprehend design challenges and are available to help select materials and manufacturing processes that best fit specific application needs.

#### **Material Solutions**

Newtop Elastomerics has strategically partnered with industry leaders such as Rogers Corp., Saint-Gobain, 3M, Wacker Silicones and Momentive Silicones to ensure the highest quality materials are used. Newtop Elastomerics has a comprehensive inventory of engineered materials designed and manufactured to meet requirements of the most demanding gasketing applications.

Pre-Production through Manufacturing
Combining in-house CNC die cutting,
waterjet cutting, injection molding,
compression molding and adhesive
lamination with comprehensive inventory,
Newtop Elastomerics can fulfill fast-turn
prototyping, pre-production and full
production requirements.

# **SNE-556**

Compound: 65 Durometer Conductive Silicone Rubber with Nickel / Graphite Filler

### **Product Description:**

SNE-556 is a silicone polymer with nickel coated graphite particle fill giving it very good shielding and grounding properties. High performance and competitively priced, SNE-556 makes an excellent option for commercial and military EMI applications.

SNE-556 has undergone significant 3rd party testing\*\* and has been approved on several defense equipment programs. Newtop Elastomerics offers pre-production and full production parts made from SNE-556, including waterjet cutting, die cutting, and molding. 3M conductive adhesive backing is also available for cut parts and select molded parts.

Property	Typical Value
Durometer, Shore "A", (+/- 5)	65
Volume Resistivity, ohm-cm	0.04
*Shielding Effectiveness, dB	>100 (@ 20MHz - 10GHz)
Tensile Strength, minimum, psi	200
Elongation, min %	200
Tear "B", min ppi	45
Temperature Low, °C (°F)	-60 (-76)
Temperature High, °C (°F)	220 (428)
Specific Gravity	1.89
Color	Black
Mil-G-83528	N/A
Available Configurations	Sheets     Cut Parts (Waterjet/Die Cut)     Molded Parts     Conductive Adhesive Backed

<sup>\*</sup>Additional data available upon request

Request Quote

<sup>\*\* 3</sup>rd party tested, method: MIL-DTL-83528D